

BRACKETERY

«802» collars



DESCRIPTION

Part of the PAM Building supporting and fixing systems, the «802» collar holds the pipework vertically to the walls. The hooking is quick thanks to the easy opening. Recommended distance between pipe and wall is 1 cm.

RECOMMENDED USE

- Domestic use
- Wastewater
- Valve water

MATERIAL


Galvanised steel

ENVIRONMENTAL DATA

- Recycling Information: 100% recyclable

BRACKETERY

«802» collars



DN	Nut	Tightening Screw	a	Weight	Product code
50	M8	Screw M6 (Key of 10)	11	0.08	251138
75	M8	Screw M6 (Key of 10)	11	0.1	251188
100	M8	Screw M8 (Key of 13)	11	0.19	251189
125	M8	Screw M8 (Key of 13)	11	0.23	251177
150	M8	Screw M8 (Key of 13)	11	0.25	251178
200	M10	Screw M8 (Key of 13)	14	0.46	255005
250	M10	Screw M8 (Key of 13)	14	0.68	255006
300	M10	Screw M8 (Key of 13)	14	0.79	255007

All dimensions are in mm and nominal weights are in kg

This document is provided for information purposes only and our company reserves the right to modify the information contained herein at any time. Our company declines all responsibility in the event of the use or installation of materials that do not comply with the rules prescribed in this document as well as with the standards, the technical documents and the applicable professional standards. Any orders placed will be subject to our General Terms and Conditions of Sale, available on request. The drawings and/or images are the exclusive property of Saint-Gobain PAM and are confidential. They must not be reproduced or disclosed to any third party without written consent. They may only be used for the purpose for which they were issued and are returnable on request.

Saint-Gobain PAM Bâtiment

21 avenue Camille Cavalier - BP 129 • 54705 • PONT-À-MOUSSON • France • Tel: +33 (0) 383 807 808 • Email: tcbatiment.sgpam@saint-gobain.com • www.pambuilding.com
Société par action simplifiée au capital de 6 812 970,75€ • SIREN 799 283 882 • RCS NANCY