

# **BRACKETERY**

# **Rubber-lined steel bracket**



### **DESCRIPTION**

Part of the PAM Building supporting and fixing systems, the rubber-lined steel bracket holds the pipework vertically to the walls. Hooking is quick thanks to the easy opening. The rubber lining rubber insert reduces the transmission of structure-borne noise to the building.

## **MATERIAL**

Steel with zinc

### **RECOMMENDED USE**

- Domestic use
- Wastewater
- Valve water

# **ENVIRONMENTAL DATA**

• Recycling Information: Partially recyclable

# Product Data Sheet - PAM Buiding - August 22 2022

# **BRACKETERY**

# **Rubber-lined steel bracket**





DN	Nut	Tightening Screw	a	Weight	Product code
50	M8/M10	Screw M6 (Key of 10)	84	0.1	251197
75	M8/M10	Screw M6 (Key of 10)	24	0.3	251198
100	M8/M10	Screw M8 (Key of 13)	137	0.3	251199
125	M8/M10	Screw M8 (Key of 13)	25	0.4	251200
150	M10	Screw M8 (Key of 13)	193	0.6	251201
200	M10	Screw M8 (Key of 13)	250	1.6	251202
250	M12/M16	Screw M12 (Key of 19)	316	1.8	251203
300	M12/M16	Screw M12 (Key of 19)	362	2.9	251204

All dimensions are in mm and nominal weights are in kg

This document is provided for information purposes only and our company reserves the right to modify the information contained herein at any time. Our company declines all responsibility in the event of the use or installation of materials that do not comply with the rules prescribed in this document as well as with the standards, the technical documents and the applicable professional standards. Any orders placed will be subject to our General Terms and Conditions of Sale, available on request. The drawings and/or images are the exclusive property of Saint-Gobain PAM and are confidential. They must not be reproduced or disclosed to any third party without written consent. They may only be used for the purpose for which they were issued and are returnable on request.