

RESIDENTIAL

Coupling for bend and offset



DESCRIPTION

Part of the PAM Building residential (type R) range, these couplings are specific for bend and offset. The seal is automatically made by compressing the elastomer seal ring at the time of assembly, by simply inserting the spigot into the socket.

RECOMMENDED USE

- Rainwater
- Gravitary

MATERIAL

EPDM

ENVIRONMENTAL DATA

- Percentage of Recycled Content: 99 %
- Recycling Information: Not recyclable

DN	Weight	Product Code
75	0.07	156077
100	0.1	156133
125	0.11	156187

All dimensions are in mm and nominal weights are in kg

This document is provided for information purposes only and our company reserves the right to modify the information contained herein at any time. Our company declines all responsibility in the event of the use or installation of materials that do not comply with the rules prescribed in this document as well as with the standards, the technical documents and the applicable professional standards. Any orders placed will be subject to our General Terms and Conditions of Sale, available on request. The drawings and/or images are the exclusive property of Saint-Gobain PAM and are confidential. They must not be reproduced or disclosed to any third party without written consent. They may only be used for the purpose for which they were issued and are returnable on request.

Saint-Gobain PAM Bâtiment

21 avenue Camille Cavalier - BP 129 • 54705 • PONT-À-MOUSSON • France • Tel: +33 (0) 383 807 808 • Email: tcbatiment.sgpam@saint-gobain.com • www.pambuilding.com
Société par action simplifiée au capital de 6 812 970,75€ • SIREN 799 283 882 • RCS NANCY